

CERTIFICATO


Proprietario del certificato	Italtherm S.p.a. Via Salvo D'Acquisto snc 29010 Pontenure PC ITALIA
Sito produttivo	Przasnysz
Prodotto	Collettore solare
Tipo, modello	Slim Solar 2.0, Slim Solar 2.0H Slim Solar 2.5, Slim Solar 2.5H
Norme di riferimento	DIN EN 12975:2022-06 DIN EN ISO 9806:2018-04 Solar KEYMARK Regole del programma (2022-06)
Marchio di conformità	 
Numero di registrazione	011-7S2729 F
Valido fino al	2028-06-30
Diritto di utilizzo	Il presente certificato autorizza ad utilizzare il marchio di conformità di cui sopra in relazione al numero di matricola indicato. Vedi allegato per ulteriori indicazioni.

ALLEGATO

Pagina 1 a 1

Certificato	011-7S2729 F del 2023-12-08
Dati tecnici	Cfr.scheda tecnica del verbale di collaudo di 2023-07-04, 2023-08-28, 2023-12-07 Osservazione/i: - La prova di resistenza al gelo secondo la norma DIN EN ISO 9806, paragrafo 14 non è necessaria. Secondo le indicazioni del produttore, i collettori certificati possono essere utilizzati in zone a rischio di gelo soltanto se si fa uso di un adeguato anticongelante.
Laboratorio di prova/ Ufficio di controllo	TÜV Rheinland Energy & Environment GmbH Am Grauen Stein 1 51105 Köln GERMANIA
Rapporti di collaudo	DE23KTBK 001 di 2023-07-04 DE23G9LG 001 di 2023-08-28 DE23QSMU 001 (Doc-check) di 2023-12-07



Annex to Solar Keymark Certificate					Licence Number		011-7S2729 F							
					Date issued		2023-12-07							
					Issued by		DINCertco							
Licence holder		ITALTHERM S.p.A			Country		Italy							
Brand (optional)					Web		www.italtherm.it							
Street, Number		Via Salvo D'Acquisto 10			E-mail		info@italtherm.it							
Postcode, City		29010 Pontenure (PC)			Tel		+39 523 575 611							
Collector Type					Flat plate collector									
Collector name					Power output per collector									
					Gb = 850 W/m ² , Gd = 150 W/m ² & u = 1.3 m/s $\vartheta_m - \vartheta_a$									
					0 K	10 K	30 K	50 K	70 K	110 K				
					m ²	mm	mm	mm	mm	mm				
Slim Solar 2.0					2.01	1 675	1 200	50	1 451	1 365	1 180	980	763	281
Slim Solar 2.0H					2.01	1 200	1 675	50	1 451	1 365	1 180	980	763	281
Slim Solar 2.5					2.51	2 090	1 200	55	1 812	1 705	1 474	1 223	953	351
Slim Solar 2.5H					2.51	1 200	2 090	55	1 812	1 705	1 474	1 223	953	351
Power output per m ² gross area					722	679	587	487	380	140				
Performance parameters test method		Steady state - indoor												
Performance parameters (related to A _G)		$\eta_{0, b}$	a1	a2	a3	a4	a5	a6	a7	a8	Kd			
Units		-	W/(m ² K)	W/(m ² K ²)	J/(m ³ K)	-	J/(m ² K)	s/m	W/(m ² K ⁴)	W/(m ² K ⁴)	-			
Test results		0.728	4.19	0.010	0.000	0.00	6 553	0.000	0.00	0.0E+00	0.95			
Incidence angle modifier test method		Quasi dynamic - outdoor												
Incidence angle modifier		Angle	10°	20°	30°	40°	50°	60°	70°	80°	90°			
Transversal		K _{GT, coll}	1.00	0.99	0.97	0.95	0.90	0.82	0.65	0.33	0.00			
Longitudinal		K _{GL, coll}	1.00	0.99	0.97	0.95	0.90	0.82	0.65	0.33	0.00			
Heat transfer medium for testing					Water									
Flow rate for testing (per gross area, A _G)					dm/dt	0.023	kg/(sm ²)							
Maximum temperature difference during thermal performance test					($\vartheta_m - \vartheta_a$) _{max}	80	K							
Standard stagnation temperature (G = 1000 W/m ² ; $\vartheta_a = 30$ °C)					ϑ_{stg}	200	°C							
Maximum operating temperature					$\vartheta_{max, op}$	200	°C							
Maximum operating pressure					p _{max, op}	600	kPa							
Testing laboratory		TÜV Rheinland Solar GmbH			www.tuv.com/solar									
Test report(s)		DE23KTBK 001 DE23G9LG 001 DE23QSMU 001 (Doc-check)			Dated		04.07.2023 28.08.2023 07.12.2023							
Comments of testing laboratory					Draft Ver. 6.2 (22.09.2021)									
														
DIN CERTCO • Alboinstraße 56 • 12103 Berlin, Germany Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: info@dincertco.de • www.dincertco.de														

Annex to Solar Keymark Certificate						Licence Number		011-7S2729 F					
Supplementary Information						Issued		2023-12-07					
Gross Thermal Yield in kWh/collector at mean fluid temperature ϑ_m													
Collector name	Standard Locations	Athens			Davos			Stockholm			Würzburg		
	ϑ_m	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C
Slim Solar 2.0		2 286	1 521	915	1 668	1 075	616	1 239	752	419	1 357	813	443
Slim Solar 2.0H		2 286	1 521	915	1 668	1 075	616	1 239	752	419	1 357	813	443
Slim Solar 2.5		2 855	1 899	1 142	2 083	1 342	770	1 547	939	523	1 694	1 016	554
Slim Solar 2.5H		2 855	1 899	1 142	2 083	1 342	770	1 547	939	523	1 694	1 016	554
Gross Thermal Yield per m ² gross area		1 137	757	455	830	535	307	616	374	208	675	405	221
Annual efficiency, η_a		64%	43%	26%	51%	33%	19%	53%	32%	18%	54%	33%	18%
Fixed or tracking collector		Fixed (slope = latitude - 15°; rounded to nearest 5°)											
Annual irradiation on collector plane		1765 kWh/m ²			1630 kWh/m ²			1166 kWh/m ²			1244 kWh/m ²		
Mean annual ambient air temperature		18.5°C			3.2°C			7.5°C			9.0°C		
Collector orientation or tracking mode		South, 25°			South, 30°			South, 45°			South, 35°		
The collector is operated at constant temperature ϑ_m (mean of in- and outlet temperatures). The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool Scenocalc Draft Ver. 6.2 (22.09.2021). A detailed description of the calculations is available at http://www.estif.org/solarkeymarknew/													
Additional Information													
Collector heat transfer medium								Water-Glycole					
The collector is deemed to be suitable for roof integration								No					
The collector was tested successfully under the following conditions:													
Climate class (A+, A, B or C)								A		--			
G (W/m ²) >		1000		ϑ_a (°C) >		20		H _x (MJ/m ²) >		600			
Maximum tested positive load								2000		Pa			
Maximum tested negative load								1750		Pa			
Hail resistance using ice balls (diameter)								35		mm			
Additional collector attribute(s)													
Using external power source(s) for normal operation						No		Active or passive measure(s) for self-protection				No	
Co-generating thermal and electrical power						No		Façade collector(s)				No	
Energy Labelling Information						Additional Informative Technical Data							
		Reference Area, A _{sol} (m ²)		Hydraulic Designation Code				Aperture Area, A _a (m ²)					
Slim Solar 2.0		2.01		1-H-12345-A:9.2,14800-C:20.6,1130				1.87					
Slim Solar 2.0H		2.01		1-H-12345-A:9.2,15200-C:20.6,1625				1.87					
Slim Solar 2.5		2.51		1-H-12345-A:9.2,19700-C:20.6,1130				2.35					
Slim Solar 2.5H		2.51		1-H-12345-A:9.2,18900-C:20.6,2020				2.35					
Data required for CDR (EU) No 811/2013 - Reference Area A_{sol}						Data required for CDR (EU) No 812/2013 - Reference Area A_{sol}							
Collector efficiency (η_{col})		54%				Zero-loss efficiency (η_0)		0.72		--			
Remark: Collector efficiency (η_{col}) is defined in CDR (EU) No 811/2013 as collector efficiency of the solar collector at a temperature difference between the solar collector and the surrounding air of 40 K and a global solar irradiance of 1000 W/m ² , expressed in % and rounded to the nearest integer. Deviating from the regulation η_{col} is based on reference area (A _{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806:2017.				First-order coefficient (a ₁)		4.19		W/(m ² K)					
				Second-order coefficient (a ₂)		0.010		W/(m ² K ²)					
				Incidence angle modifier IAM (50°)		0.91		--					
Remark: The data given in this section are related to collector reference area (A _{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806. Consistent data sets for either aperture or gross area can be used in calculations like in the regulation 811 and 812 and simulation programs.													
DIN CERTCO • Alboinstraße 56 • 12103 Berlin, Germany													
Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: info@dincertco.de • www.dincertco.de													